


MB102 PCB Terminal Block, Modular



MB

DIMENSIONS/POSITIONS

MB102-750M

間距	Pitch	7.50mm
位數	Poles	1Poles
塑膠本體	Housing Material	PA 66
壓線圈	Cage Clamp	Brass, Ni Plated
端子	Contact	Brass, Tin Plated
螺紋	Screw Thread	M3.0, Steel, Zinc Plated
電線線徑	Wire Size	10 ~ 24AWG
剝線長度	Wire Strip Length	6mm ~ 7mm
PCB孔徑	PCB Hole Diameter	1.3mm
最大緊固扭矩	Tightening Torque, Max.	3.56 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C

TECHNICAL DATA

連接符合標準	Connection in acc. with standard EN-VDE	
額定電流 I _n	Nominal Current I _n	30A
額定橫截面	Nominal Cross Section	4.0mm ²
最大負載電流	Maximum load current	30A
絕緣材料	Insulating Material	PA
阻燃等級,符合UL94	Inflammability class acc. to UL94	
		V0
額定電壓,UL/CUL	Nominal voltage, UL/CUL	
		300V
額定電流,UL/CUL	Nominal current, UL/CUL	
		30A

